



【 HFC-A25000 】 series

Magnetic Absorber TDS



- Product picture -

Smaller and thin are required with the development of electronic products, it is more important to RFID anti-metal reader and tag, EMI component, Wireless charge products and Electro Magnetic Screen technology etc. Absorber material appeared to solve this problem. It has ultra-thin, soft, easily to roll up and cut performances, it can be custom-made, and also available for laminate with shielding materials like metal foil and fabrics as a multi-layers constructions.

FEATURES:

- Soft and ultra-thin
- Insulation properties
- Available in very narrow spaces
- Flexible to cut various shapes
- Excellent performances of absorb electromagnetic radiation noise
- High stickness guaranteed install reliability

APPLICATIONS:

- EMI component
- RFID anti-metal electronic tags and NFC
- Wireless charge products
- Magnetic screen technology

REMARKS:

The material can be laminated with shield layer, Available for custom-made.

The series of products accord with standers of ROHS and HALOGEN.

PROPERTIES

Items	Parameter	Test Method
Permeability (μ' @3MHz)	250	IEC 62044-1:2002
Thickness (mm)	0.03~0.1	—
Surface resistance (Ω/inch^2)	$\geq 10^6$	ASTM D257
Adhesion strength (kgf/inch)	≥ 1.0	—
Frequency range (Hz)	EMI: 100MHz~3GHz	—
Operating temperature ($^{\circ}\text{C}$)	-25~120	—
UL Certify	UL94V-0	—
Package	Sheet	—

All above data are copyrighted and elaborated by HFC

Magnetic Absorber Properties Test Methods:

The Permeability VS Frequency:

